

BERKELEY® B-SERIES 50 & 60 HZ

COMMERCIAL CENTRIFUGAL PUMPS



PUMPS
50 & 60 HZ

COMMERCIAL

FEATURED HIGHLIGHTS

Where a large volume of water is needed, in flooded suction applications, Berkeley brand pumps can accommodate almost any water-moving needs. Berkeley brand pumps have been one of the top names in the water systems for decades. Once recognized for only being affiliated with irrigation and water systems, Berkeley pumps are now available in many configurations to be used in the following applications:

- Water features
- Water parks
- Aquaculture
- Commercial pools and spas

The pumps pictured above and included in the chart below show just a small sampling of the many pump sizes and designs that are available. In addition, we offer a wide range of gpm/head configurations; 1200, 1750, or 3450 rpm motors; 50 or 60 Hz; optional high-efficiency motors; voltage, horsepower, and service factor options; lead-free bronze impellers; flange or threaded connection in many sizes; and packing or mechanical shaft seal design pumps. Flooded suction required.

ORDERING INFORMATION

Product	General Pump Design Model	HP	Best Operating Performance G.P.M.	Connection at X ft. of Head	RPM	Flange (inches)
BERKELEY B-SERIES PUMPS						
B71943S	B3ZPMS	5 HP	350	40	1800	3 x 4
B71945S	B3ZPMS	7.5 HP	400	53	1800	3 x 4
B71947S	B3ZPMS	10 HP	500	60	1800	3 x 4
B71949S	B3ZPMS	15 HP	600	63	1800	3 x 4
B76775	B5EPHS	20 HP	950	60	1800	5 x 6
B76776	B5EPHS	25 HP	1050	65	1800	5 x 6
B75861	B4GPBHS	30 HP	1100	85	1800	4 x 6
B74945	B6JPBMS	40 HP	1500	80	1800	6 x 8
B76786	B8GPBMS	50 HP	2700	50	1800	8 x 10

Options: The above pumps have silicon bronze impellers, flanged connections, close-coupled, open drip-proof motors, and mechanical shaft seals. As mentioned in the text at the top of the page, many options are available. Please call our Customer Service at 800-831-7133 or try using the convenient "BEC" system at www.berkeleypumps.com.

BERKELEY® B-SERIES 50 & 60 HZ (CONT'D)

COMMERCIAL CENTRIFUGAL PUMPS

Part Name	Material	Spec Number
MATERIALS OF CONSTRUCTION		
Volute Case	Cast Iron	ASTM A48 Class 30
Wear Ring	Bronze	ASTM B584 (UNS C87500)
Impeller	Cast Iron	ASTM B854 (UNS C87500)
	Bronze (optional)	
Seal Retainer	Cast Iron	ASTM A48 Class 30
Adaptor Bracket	Cast Iron	ASTM A48 Class 30
Shaft Sleeve	416 S.S.	AISI 416SS
Lantern Ring	Teflon	
Mechanical Shaft Seal	18-8 S.S.metal parts; "Buna-N"rubber bellows, ceramic stationary, carbon rotating face	
Packing Gland	Stainless Steel	AISI 304
	Cast Iron	ASTM A48 Class 30
Packing	PTFE packing with graphite impregnation	
Close Coupled Motor Shaft	Carbon Steel	AISI C1045

COMMERCIAL
PUMPS
50 & 60 HZ

